

MILOS WHITE SL

SKINLAM®







MILOS WHITE

Ослепительно белый фон Milos White служит сценой для игривого развертывания его тонкой серой прожилки. Керамический материал, создающий стиль.

ПОВЕРХНСТИ



NATURAL

ФОРМАТЫ

ТОЛЩИНА	3000 x 1000 mm	3000 x 250 mm	1500 x 1000 mm	1000 x 1000 mm	500 x 1000 mm	200 x 1000 mm	500 x 500 mm	300 x 500 mm
3 mm	•		•	•	•		•	•
3 + mm	•		•	•	•		•	•
5 mm	•		•	•	•		•	•
5 + mm	•		•	•	•		•	•
3 + 3 mm	•		•	•	•		•	•

ПРИМЕНЕНИЕ



внешняя облицовка



ВНУТРЕННЯЯ ОБЛИЦОВКА



внутренний пол



НАРУЖНАЯ УКЛАДКА ТРАТУРАРА



СТОЛЕШНИЦЫ ДЛЯ ВАННОЙ



СТОЛЕШНИЦЫ ДЛЯ КУХНИ

ПРЕИМУЩЕСТВА



ГИГИЕНИЧЕСКАЯ ПОВЕРХНОСТЬ



долговечные неизменяющиеся цвета



Устойчивость к пятнам



УСТОЙЧИВЫЙ К ХИМИКАТАМ



ОГНЕ- И ТЕРМОСТОЙКОСТЬ





УСТОЙЧИВЫЙ К ЦАРАПИНАМ



экологически чистый



PEI

5



Характеристики	Стандарты испытагий	Значение			
Водопоглощение (%)	'				
3 mm	UNE EN 10545-3	0,1			
5 mm		0,1			
Прочность при изгибе (N/мм2)		Прочность при изгибе	Прочность при разрыве		
3 mm	UNE EN 10545-4	57	330		
5 mm		63	1011		
Стойкость к истиранию (PEI)	UNE EN 10545-6	Class !	5		
Сопротивление ударам путем измерения коэффициента реституции					
3 mm	UNE EN ISO 10545-5	0,77			
5 mm		0,84			
Морозостойкость мин. 150 циклов	UNE-EN 10545-11	Без по	вреждений		
Химическая стойкость (Класс)	UNE EN 10545-13	GLA,	GHA		
Устойчивость к пятнам (Класс)	UNE EN 10545-14	Class !	5		
Сопротивление скольжению (маятник) (USRV)	UNE-EN 12633	< 35			
Светостойкость и устойчивость цвета керамической плитки	DIN 51094	DIN 51094 Без повреждени			
Огнеупорность	Решение комиссии 96/603/ЕС	горючие			

*Имеется декларация соответствия EC

Мы предлагаем материалы с характеристиками, которые могут адаптироваться к вашим требованиям.

ИСПОЛЬЗОВАНИЕ ПО ТОЛЩИНЕ

	3 mm	3+ mm	5 mm	5+ mm	3+3 mm
Внутренние стены nterior walls	•	•	•	•	•
нутренние полы nterior floors	_	_	•	•	•
Наружные стены xterior walls	_	•	•	•	•
Іаружные полы xterior floors	_	_	_	_	•
ентилируемые фасады с видимыми анкерами entilated facades seen anchors	_	•	_	•	•
толешницы ountertops	_	_	_	_	_
олы с повышенной нагрузкой и проходимостью igh transit floors	_	_	•	•	•
еконструкция поверх существующих стен Refurbishment rectly over existing walls	•	•	•	•	•
линтус kirting	_	•	•	•	•
омпозитные панели (алюминий, фанера, гипсокартон) omposite panels (aluminium, plywood, plasterboard)	•	•	•	•	•
конструкция непосредственно над существующими этажами efurbishment directly over existing floors	_	•	•	•	•

ПРИМЕНЕНИЕ ПО КОЛЛЕКЦИЯМ

	Basic	Blaze	Deco	Hydra	Slate	Steel	Stone	Vulcano	Wood
ПОЛЫ	•	•	•**	•	•	•	•	•	•
СТЕНЫ	•	•	•	•	•	•	•	•	•
ФАСАДЫ	•	•	•	•	•	•		•	
МЕБЕЛЬ	•	•	•**	•	•	•	•	•	
СТОЛЕШНИЦЫ	•	•	•**	•				•	•

ПОВЕРХНОСТИ ПО КОЛЛЕКЦИЯМ

	Basic	Blaze	Deco	Hydra	Slate	Steel	Stone	Vulcano	Wood
Satin / Сатинированная	•	_	•	•	_	_	_	•	_
Natural / Натуральная	_	•	•**	_	•	•	•	_	•
Bush Hammered / Бучардированная	_	_	•***	* –	_	_	•***	_	_
Matt / Матовая	_	_	•***	_	_	_	_	_	_

^{*}Только на полах с идеальной планиметрией и без высоких нагрузок.

^{*****}Tолько Silk.

QUALITY AND ENVIRONMENT CERTIFICATES*



- · It can be ground down and used in other production processes.
- The relative thinness of Techlam (3 or 5mm) compared to a traditional tile (10mm) reduces the environmental impact of the production process, by using less raw materials, energy and water and also reduces transport costs.

· Miembro del US Green Building Council

Organización sin ánimo de lucro que vela por:

- · La construcción de edificios sostenibles.
- · El uso de materiales sostenibles para la construcción de edificios.
- El establecimiento de los estándares y criterios del sistema de certificación LEED de construcción sostenible.

· Member of the US Green Building Council

A non-profit organisation which oversees:

- · The construction of sustainable buildings
- \cdot The use of sustainable materials in the construction of buildings
- · The establishment of standards and criteria for the LEED certificate for sustainable construction.





Product contains recycled material

Recycled material has been used as a raw material, so using Techlam has the following benefits:

- \cdot The environmental impact of extracting and processing the raw materials is reduced.
- · It provides a solution to the demand for products containing recycled material for sustainable construction projects.

Self-declared environmental claims of the content of recycled available.

· The Environmental Product Declaration (EPD)

It is a type-III environmental certification that includes reliable, relevant, transparent and verified environmental information on all the environmental impacts that Techlam and natural stone can generate during their lifecycle. This Declaration is based on the EN ISO 14025:2010 International Standard and was therefore verified during the audit conducted by AENOR experts in our facilities.





GREENGUARD Certificates

This certificate ensures that construction products for indoor use comply with strict emission limits based on tests and guidelines of the National Toxicology Program of the United States. The benefits of using Techlam are:

- · It improves the quality of indoor air which makes it ideal for use in enclosed spaces.
- The GOLD certificate states that Techlam is an ideal material for indoor spaces particularly where children and sensitive adults spend extended periods of time, such as schools and healthcare facilities.
- It provides a solution to the demand for construction products containing recycled material for sustainable construction projects.
- · It is a programme recognised by the US Green Building Council.



A+ Indoor Air Quality

Techlam has obtained the highest classification, A+, as the levels of hazardous substances released are well below the limits in the applicable guidelines. The benefits of using Techlam are:

- · It protects environmental quality in enclosed spaces and improves levels of comfort and wellbeing for installers, occupants and users.
- It provides a solution to the demand for products for sustainable construction projects.
- · It complies with the French Government Regulation for construction products.

^{*} Certificates available

CERTIFICADOS DE CALIDAD Y MEDIO AMBIENTE* | QUALITY AND ENVIRONMENT CERTIFICATES*





· EC

With the statement of EC conformity, it is thereby stated that the product that is sold conforms with the regulatory requisites of the harmonized rules or technical specifications according to the application and anticipated use of the product, in accordance with European Regulation on Construction Products (EU) No. 305/2011.

· AIDIMA Quality Symbol

TECHLAM® has obtained the Quality Symbol by The Technology Institute on Furniture, Wood and Packaging (AIDIMA), certifying this thin ceramic tile as a suitable product for its use in the furniture manufacture.





- ASTM

ASTM (American Society for Testing and Materials) is the institution that is in charge of developing the law on the testing and characterization of materials in the United States, thereby establishing the minimum requisites for the uses anticipated for each material.

· CCC Certificate

The China Compulsory Certification (CCC) is a compulsory safety mark granted by Certification and Accreditation Administration of the People's Republic of China (CNCA) for the marketing of products in China.



· ISO 9001

The ISO 9001 Quality Certificate confirms the successful implementation of a new quality management system in the TECHLAM® factory.

* Certificates available



BREEAM°

Certification systems for sustainable construction

Using Techlam in a construction project contributes to obtaining points for the sustainable construction certificate. The best-known certification programmes internationally are:

- LEED (Leadership in Energy & Environmental Design), developed by US Green Building Council.
- · BREEAM (Building Research Establishment Environmental Assessment Methodology) developed by BRE (Building Research Establishment) in the United Kingdom.





Tel. +7 495 258-56-55 Tel. +7 495 258-56-60 dg@duvils.ru www.duvils.ru